

fireworks24rain[®] & fireworks24case[®]

Our newest product **fireworks24rain[®]** was tested in permanent installation during a four-year practice by the most different teams of professional pyrotechnicians at home and abroad on the occasion of various fireworks festivals. Developed especially with concern to big fireworks additional new possibilities of application are made accessible to the manufacturers of pyrotechnics by **fireworks24rain[®]**. Guarantor of the suitability for daily use: For all professional pyrotechnicians of our test series now itself an indispensable product of our daily work! Whatever sun or rain, hail or snow, **fireworks24rain[®]** protects reliably your fireworks installations against all weather conditions. In addition **fireworks24rain[®]** in its capacity as stable protection against over-igniting is an extremely effective medium practically to use.

The VK units are delivered with approx. 50 m **fireworks24rain[®]** in each case on stable board core rolls. On request additionally available also in **fireworks24case[®]**, of course, weatherproof and on special request with cutting unit inside.



JUP Fireworks EUROPE LTD

D-office: Katharinenstraße 2 • 99817 Eisenach • Germany
D-contact: phone +49 (0)3691 222172 • fax +49 (0)32223748454
Mobil: +49 (0)162 4823455
Internet: www.fireworks.de • **E-Mail:** JUP24@t-online.de



Technical data of **fireworks24rain[®]**

Paper: Albino type, 49 g/m²
 Paper*: length about 50 m,
 Width 990 mm,
 Ø 110 mm (outside)
 Coating: inside, polyethylene (PE),
 12 g/m²
 Coating: outside, aluminium,
 9 µm
 Board core*: length 1.000 mm,
 Ø 70 mm (outside)
 Weight*: about 5 kg

made by **JUP Fireworks EUROPE LTD**, Germany

Technical data of **fireworks24case[®]**

External dimensions*: length 1.090 mm
 Width 240 mm,
 Height 240 mm
 Internal installation*: bayonet mount for
fireworks24rain[®]
 Cutting unit
 Weight*: about 5 kg

Made by **JUP Fireworks EUROPE LTD**, Germany

* Technical data are subject to changes from improvement of our products